

CP4000 extremepower

CP2900

CP2500

CP1800



CP2500

CP1500
Accessori opzionali



Caratteristiche tecniche
Technical specifications

	CP4000	CP2900	CP2500	CP1800		CP4000	CP2900	CP2500	CP1800
Peso e scavatore - Excavator weight	t 34-55	29-45	26-40	18-29	lbs	74800-121000	63800-99000	57200-88000	39600-63800
Peso attrezzatura - Crusher weight	Kg 3950	3000	2500	1800	lbs	8690	6600	5500	3960
Forza cilindro - Cylinder Force	t 140	130	115	80	lbs	308000	286000	253000	176000
Pressione di esercizio cilindri - Working Pressure	bar 350	350	350	350	psi	5075	5075	5075	5075
Pressione di esercizio Rotazione M AX - Working Pressure M AX	bar 120	120	100	190	psi	1740	1740	1450	2755
Portata olio cilindri - Cylinder Oil flow	l/min 300-350	250-300	160-220	150-200	gpm	79-92	66-79	42,3-58,2	39,6-52,9
Portata olio rotazione - Rotation Oil flow	l/min 50	50	10-15	30	gpm	13	13	2,64-3,96	7,9
Apertura ganasce - Jaw Opening	mm 1230	1100	880	750	in	48,42	43,31	34,64	29,52
Profondità Cutter - Cutter Depth	mm 580	520	500	340	in	22,83	20,47	19,68	13,38
Profondità Crusher - Crusher Depth	mm 960	880	690	580	in	37,79	34,64	27,16	22,83
Altezza Totale - Total height	mm 2600	2370	2650	1930	in	102,36	93,30	104,33	75,98
Rotazione a 3 60° - 3 60° Rotation	Idraulica	Idraulica	Idraulica	Idraulica		Hydraulic	Hydraulic	Hydraulic	Hydraulic